

SEA TEL 120 TV

3-Axis marine stabilized antenna system ready for worldwide Ku-Band HD reception

Product Sheet

The most important thing we build is trust

COBHAM

The Sea Tel 120 TV antenna system features advanced technology that enables the user to receive Ku-Band High Definition satellite services worldwide without ever having to change the LNB. With our simple to use MMI, changing satellite services is as simple as a few button clicks away.

With advanced stabilization, the Sea Tel 120 TV is made for extreme conditions. Whether at dockside, anchor or rocking and rolling on the 7 Seas, the Sea Tel 120 TV is the right antenna for watching your favorite satellite TV programming.

Key Features & Benefits

- Programmable LNB that receives worldwide Ku-Band services. No more changing LNB's when travelling to different regions of the world.
- Advanced stabilization for viewing satellite TV even in rough sea conditions.
- Integrated DVB-S2 tuner for reception and identification of DVB-S2 and DVB-S satellite broadcasts.
- Frequency tuned radome minimizes signal loss.
- Easy installation and use. Uses same bolt pattern as the Sea Tel Series 04 systems.
- Extensive capabilities for online and offline troubleshooting.
- Intuitive and secured user interface with extensive data logging capabilities.
- Worldwide service along with 2 years parts and 2 years labor warranty (Flex warranties available).
- Built to last in extreme conditions.
- Global satellite library.



SEA TEL 120 TV

3-Axis marine stabilized antenna system ready for worldwide Ku-Band HD reception


Typical Data for the Sea Tel 120 TV

SPECIFICATIONS

Min. EIRP Ku-Band	40.5 dBW
Dish Diameter	124.46 cm (49 in)
Radome Diameter	166.88 cm (65.7 in)
Radome Height	178.31 cm (70.2 in)
ADE Weight	115.67 kg (255 lbs.)
Operating Temperature Range	-20° C to 55° C
Storage Temperature Range	-40° C to 70° C
Pedestal Type	3 Axis (Azimuth, Elevation, Cross Level)
Ships Motion	Roll +/- 25°; Pitch +/- 15°
Turning Rate	15° deg /sec @ 5° deg /sec ²
Azimuth Range	680°
Elevation Range	-15° to 115°
Polarization	Linear/Circular Selectable
Stabilization Accuracy	0.2° Peak error under specified ship's motion
Skew Control	Automatic
LNB Type	Ku-Band Worldwide Programmable
Frequency Range	Ku-Band (10.7 - 12.75 GHz)
Warranty	2 years parts / 2 years labor

Typical Data for Lite Media Exchange Point (LMXP)

- Standard 19 inch 1U rack mount
- 43.18 cm x 25.4 cm x 4.44 cm (17" x 10" x 1.75")
- 110/220VAC, 47-63 Hz, Single Phase
- 2.45 kg (5.4 lbs)
- 2 Ethernet Ports
- 1 F-type connector
- 8 Tri-colored MXP status LED's
- USB Device (Mini B)
- 1 RS-232 pass through port
- 1 NMEA RS-232 serial port
- 1 RS-232 Console Port
- Aux IN1 & Aux IN2
- SW1, SW2 (I/O)
- 1 Gigabit SFP Ethernet



For further information please contact:

www.satcom.ohc@cobham.com